



SERIES 7200

Precision Pressure Indicator

- Pressure ranges from 15 to 40,000 psi
- Precision to 0.01%
- Six pressure ranges available in one instrument
- User defined configurations allow one instrument to perform multiple tasks and functions
- Large, easy to read display
- AC or battery operation for portability



SERIES 7200

Precision Pressure Indicator

The Series 7200 is Ruska's latest, third generation, Precision Pressure Indicator (PPI) which includes several new features, from the large text and graphics display to the easy to use menu.

Flexibility and Performance

The Series 7200 consists of two models: the Model 7220 and the Model 7230. Each model is available in a dual sensor configuration for enhanced performance (7222 and 7232 respectively). The Model 7220 and 7222 provides cost effective measurement from 19 psia (ideal for barometric measurement) to 750 psia with a precision of up to 0.01% full scale. Ranges of 19, 38 and 50 psia can be used with virtually any noncorrosive gas whereas ranges of 150, 500 and 750 psia are for use on either air or nitrogen. The Model 7230 and 7232 provide a greater range of pressure measurement capability with ranges from 15 psia to 40,000 psia. Additionally, the 7230 and 7232 are available with the Triple Scale option providing up to six measurement ranges in a single instrument, with precision up to 0.01% of each range. The 7230 and 7232 can be used with virtually any noncorrosive gas for all ranges. Ranges of 1000 psia and higher can be provided with a liquid filled test port for measurement applications where the test media is a liquid instead of a gas.

Large, Bright Display

The Series 7200 features a backlit, LCD display with a large character size allowing the pressure value and units to be read from several feet away, especially useful when utilizing the Series 7200 as a lab barometer. All aspects of the display can be customized by the user (for example, the upper part of the display can show the pressure reading and the lower display can be set to show the rate of pressure change in units per minute or per second).

Pressure Units

The PPI can display pressure in 18 different units including: psi, inHg @ 0°C, Pa, hPa, kPa, MPa, inH₂O @ 4, 20 and 25°C, cmH₂O @ 4°C, kg/cm², mmHg @ 0°C, bar, mbar, psf, atm, feet and meters. There are also two user defined units. Knots and km/hr are available on dual sensor instruments.

Tare Mode

The PPI has the ability to "tare" the sensor reading at any value. This is especially useful when using an absolute range PPI in gauge mode.

Peak Hold

The Series 7200 will retain the lowest and highest measured pressure since the last reset. This is a useful feature when using the Series 7200 to set and test relief valves and pressure switches.

Leak Test

The Series 7200 has a built in function to allow the operator to easily perform a leak test. The user can define a wait or dwell time prior to initiating the leak test along with defining the amount of time to perform the test. At the completion of the test the Series 7200 will display the change in pressure along with the rate of pressure change.

Programmable Limits

The PPI allows the operator to set user defined high and low pressure limits. Should the measured pressure exceed these limits, an audible alarm will sound.



Use the PV-411 Hand Pump along with the optional Series 7200 Carrying Case and battery for a portable calibration system.



Or, use the manual Pressure Control Pack with the Series 7200 to configure a bench top calibration system.



Profiles

The Series 7200 is capable of storing up to 4 user defined profiles. A profile is used by the PPI to save a display configuration for future recall. This way, the most commonly used configurations can be easily created and recalled with a minimum of key strokes. For example, a user may have a dual sensor PPI that is used in two primary applications. One may be for testing avionics devices in units of feet of altitude and knots of airspeed whereas the second application may be a single channel operation for measuring barometric pressure in units of inHg. The user could set up the unit for the first application with a profile named AVIONICS and a second named BARO. Switching between these two settings or profiles only requires two keystrokes.

Airfield Mode

The PPI can be set up to operate in either Standard or an Airfield mode of operation when utilized as a barometer. The Standard mode is used for most applications; however, the Airfield mode can be used where the operator wishes to correct the pressure reading for a particular airfield elevation and air temperature (both QFE and QNH are supported).

Three Hour Trend Graph

The Series 7200 has the ability to log and display a three-hour trend graph. Graph scaling occurs automatically with the X axis set at 3 hours, and the Y axis set at the maximum and minimum pressures that occurred during the previous 3 hour window.

Battery Operation

An optional rechargeable battery is available for using the PPI in remote locations where AC power may not be available. No other instrument provides the range of performance and pressure range in a battery powered instrument. The battery is approved by the Department of Transportation (DOT) and the International Air Transport Association (IATA). The battery is easily installed and typically provides over 8 hours of operation and is automatically recharged when the PPI is connected to AC power. Alternatively, an optional external battery charger is available. A screen saver function is included to turn off backlighting when the PPI is not in use to extend battery life.

Triple Scale Option

The Model 7230 single sensor PPI and Model 7232 dual sensor PPI are available with the Triple Scale option. This option enhances the performance of the PPI over a greater pressure range turning the 7230 into a three range instrument and the 7232 into a six range instrument reducing the number of instruments required to cover a wide pressure range. The table (left) shows the ranges provided with each full scale sensor range.

Full Scale	Triple Scale Ranges (psia)		
	Low	Mid	High
15	5	10	15
23	7	15	23
30	10	20	30
45	15	30	45
100	30	60	100
200	50	100	200
300	100	200	300
500	150	300	500
1000	300	600	1000
2000	600	1200	2000
3000	1000	2000	3000
6000	2000	4000	6000
10,000	3000	6000	10,000
20,000	6000	12,000	20,000
30,000	10,000	20,000	30,000
40,000	12,000	25,000	40,000

Computer Interface

The PPI is provided with an RS-232 interface for connecting to a PC. An optional IEEE-488 interface plug-in card is also available. Both interfaces support SCPI (Standard Commands for Programmable Instruments) and can emulate the older Ruska Series 6200 PPI for easy upgrade.

Specifications

PRESSURE RANGES

Model 7220	19, 38, 50, 150, 500 and 750 psia
Model 7222	Select any two of the above 7220 ranges
Model 7230*	
Absolute	15, 23, 30, 45, 100, 200, 300, 500, 1000, 2000, 3000, 6000, 10,000, 20,000, 30,000 and 40,000 psia
Gauge	15, 30, 100 and 200 psig
Model 7232*	Select any two of the above 7230 ranges

*All ranges can be Triple Scaled (see table)

PERFORMANCE

Precision¹

Model 7220	
Ranges 19, 38 and 50 psia	0.01% full scale
Ranges 150, 500 and 750 psia	0.02% full scale
Model 7230	
Ranges to 20,000 psia	0.01% of range
Ranges 30,000 and 40,000 psia	0.02% of range

Stability

Model 7220	0.01% of full scale per year
Model 7230 to 20,000 psia	0.01% of range per year
30,000 and 40,000 psia	0.02% of range per year

Total Uncertainty²

Model 7220	
Ranges 19,38 and 50 psia	0.014% full scale per year
Ranges 150, 500 and 750 psia	0.028% full scale per year
Model 7230	
Ranges from 15 to 20,000 psi	0.015% of range per year
Ranges 30,000 and 40,000 psi	0.028% of range per year

Display Resolution

User selectable to 1:1,000,000

Calibrated Temperature Range

All models and ranges 0 to 50 °C

Media

Model 7220:	
Ranges 19,38 and 50 psia:	Any noncorrosive gas
Ranges 150, 500 and 750 psia:	Air or Nitrogen
Model 7230:	Any noncorrosive gas, or specify silicone oil filled test port for use with liquid systems for ranges 1000 psia and higher

OPTIONS

IEEE-488 interface card
 Battery
 Battery Charger
 Carrying case
 Rack Mount Kit

GENERAL

Display

Vacuum fluorescent, graphical

Electrical Power

110/220 VAC, 50/60 Hz

Communication

RS-232 standard, IEEE-488 optional

Temperature

Operating : 0 to 50 °C
 Storage : -20 to 50 °C

Humidity

5% to 95% relative humidity, non-condensing

Dimensions

4.75" H x 11.75" W x 13" D

Weight

9 lb.

Test Port Connection

1/4 inch NPT female for ranges to 500 psi
 1/8 inch NPT female for ranges above 500 to 10,000 psi
 1/8 inch Autoclave for ranges above 10,000 to 40,000 psi

1 Precision is defined as the combined effects of linearity, repeatability hysteresis and temperature effects over the entire operating temperature range (0 to 50 °C).

2 Expression of accuracy (uncertainty) conforms with the recommendations of the ISO Guide to the Expression of Uncertainty in Measurement and includes precision, stability, temperature effects, and the calibration standard.

Due to Ruska Instrument's process of continuous improvements, printed specifications are subject to change without notice.

Other Products and Services

In addition to a wide range of digital pressure controllers and indicators from 1 to 40,000 psi, Ruska manufactures primary standard deadweight gauges from 0.2 to 72,500 psi.



Representative:



Ruska Instrument Corporation

P.O. Box 630009, Houston, TX 77063-0009

(713) 975-0547 ■ Fax (713) 975-6338

E-mail: ruska@ruska.com ■ <http://www.ruska.com>

 A Druck Company

© 2000 Ruska Instrument Corporation. Ruska is a trademark and the Ruska logo is a registered trademark of Ruska Instrument Corporation. All rights reserved.